

# Delta Bar Range

ECE R65 Approved



## Features and Options:

A range of high quality low profile light bars for amber and blue markets. Xenon, xenon/LED and Full LED variants are available.

- Dual voltage 12/24V
- Single flash Xenon corner strobes
- Intensely bright 3rd generation LED corners
- Xenon face strobes feature a choice of high visibility ripple flash pattern
- LED face modules feature a unique high visibility tri-phase flash pattern
- Five lengths available: 520, 750, 980, 1200 and 1430
- Aluminium box extrusion with front and rear face modules
- Long life Xenon flash tubes and LED modules
- Low power consumption
- Easily installed and removed magnetic mount version for a range of 520 and 750mm bars. Please call for further information
- 12 months' guarantee

## Mounting Options:

- Standard mount consists of four rubber feet. Side mounting kit available for specific applications.

## Applications:

Suitable for all sectors of the commercial vehicle market and emergency services.

## Materials:

Polycarbonate lens covers, aluminium box extrusion.







|                             |                                |         |              |      |
|-----------------------------|--------------------------------|---------|--------------|------|
|                             |                                |         |              |      |
| <b>Xenon corner strobes</b> | >100cd (amber)<br>>42cd (blue) | 120/min | single flash | IP65 |
|                             |                                |         |              |      |
| <b>LED corner strobes</b>   | >100cd (amber)<br>>50cd (blue) | 120/min | quad flash   | IP65 |

Certified to EMC directive 2004/104/EC.

Certified to ECE R65 (Xenon – amber and blue, LED – blue only).

High voltage transient and polarity reversal protection fitted.

Operating temperature: -20° to +55°C.



# Maxisafe

Standard light bar for the recovery, rescue and road maintenance markets. Incorporating full Xenon strobes and highly visible ripple flash pattern to the rear face of the light bar.



Maxisafe 4DB front and rear








| Product             | Length (mm) | 12V    | 24V    |        |       | Each bar shown front & rear (front at the top) |
|---------------------|-------------|--------|--------|--------|-------|--|
| <b>Maxisafe 4DB</b> | 1200        | 880074 | 880073 | 12.86A | 6.44A |  |
| <b>Maxisafe 5DB</b> | 1430        | 880075 | 880072 | 15.09A | 7.56A |  |

**LED** Enhanced Delta Bar with Xenon strobe corners and LED modules. Tri-phase flash pattern to front and rear.



5DB LED (front and rear are identical)

| Product     | Length (mm) | Dual Voltage | <i>i</i> 12V | <i>i</i> 24V | Each bar is identical front and rear  |
|-------------|-------------|--------------|--------------|--------------|---|
| LED/LED 1DB | 520         | 880410       | 4A           | 2A           |  |
| LED/LED 2DB | 750         | 880420       | 5.2A         | 2.8A         |   |
| LED/LED 3DB | 980         | 880430       | 6.4A         | 3.2A         |   |
| LED/LED 4DB | 1200        | 880440       | 7.6A         | 5.6A         |   |
| LED/LED 5DB | 1430        | 880450       | 8.8A         | 4.4A         |  |






**Maxi-LED** Featuring corners fitted with 3rd generation high brightness LEDs, quad flash pattern.



**NEW** LED corner module



5DB LED (front and rear are identical)

| Product     | Length (mm) | Dual Voltage | <i>i</i> 12V | <i>i</i> 24V | Each bar is identical front and rear  |
|-------------|-------------|--------------|--------------|--------------|---|
| LED/LED 1DB | 520         | 880510       | 2.8A         | 1.4A         |  |
| LED/LED 2DB | 750         | 880520       | 4A           | 2A           |   |
| LED/LED 3DB | 980         | 880530       | 5.2A         | 2.6A         |   |
| LED/LED 4DB | 1200        | 880540       | 6.4A         | 3.2A         |   |
| LED/LED 5DB | 1430        | 880550       | 7.6A         | 3.8A         |   |