

LP Synchronous Flash LP4XDV/2 SYNC (2watt) and LP4XDV/5 SYNC (5watt)



| | | | | | | |
|-----------|--------|--------------|------------------------|-----------------------|------|--------|
| | | | | | | |
| see table | 75/min | single flash | 2W: 192mA 5W: 333mA | 2W: 96mA 5W: 220mA | IP67 | 100gms |

Features:

A compact directional Xenon beacon with synchronous flash capability.

- Dual voltage 12/24V (10 – 30Vdc)
- Synchronous flash capability
- Vibration protected circuit
- 2W and 5W versions available
- 12 months' guarantee

Applications:

Suitable for many vehicle applications including fleet, cars, delivery, refuse trucks, large vehicles, road maintenance, recovery, utilities, road safety, plant and contracting.

Materials:

Polycarbonate lens and base.

Certified to EMC directive 2004/104/EC.

High voltage transient and polarity reversal protection fitted.

Operating temperature: -20°C to +55°C.

| Lens Colour | Power | Light Output | Part Number |
|-------------|-------|--------------|-------------|
| Clear | 2W | 50cd | 442001 |
| | 5W | 85cd | 439001 |
| Amber | 2W | 25cd | 442002 |
| | 5W | 45cd | 439002 |
| Red | 2W | 11cd | 442003 |
| | 5W | 19cd | 439003 |
| Blue | 2W | 10cd | 442004 |
| | 5W | 18cd | 439004 |
| Green | 2W | 10cd | 442005 |
| | 5W | 18cd | 439005 |

