

Orion 3XMV/LED

Patent Pending / Registered Community Design / US Design Patent



CE – certified to EMC directive 2004/108/EC.
 Complies with low voltage directive 2006/95/EC.
 High voltage transient and polarity reversal protected.
 Operating temperature: -20°C to + 50°C.
 Beacon should be operated in a vertical position with lens uppermost.



15cd	65 flashes/min 6 bursts/flash	10-100Vdc	350mA	60mA	IP65	0.31 kg

Features:

A bright, multivoltage, amber LED beacon with low power consumption.

- Multivoltage 10 – 100 Vdc
- Clear lens with amber coloured LEDs
- Bright, intense '6 burst' LED flash
- Low power consumption
- 3 year guarantee
- Weatherproof to IP65

Product options:

- European 130mm PCD hole pattern to ISO 4148
- US 118mm (4 5/8") PCD hole pattern
- Sounder plinth, fixes to base of beacon



FX29 Sounder Plinth
Part No. 521047

Applications:

Suitable for fork lift trucks and battery powered vehicles.

Materials:

Polycarbonate lens, EVA/PVC base.
 Product is ROHS compliant.

Amber	498001	498010
	Europe	USA
	<p>Drilling for Panel Mounting (ISO 4148)</p> <p>4 holes 7mm dia.</p> <p>120°</p> <p>120°</p> <p>Cable entry</p> <p>← 130 mm dia. →</p>	<p>Drilling for Panel Mounting (USA Hole Pattern)</p> <p>4 holes 6mm (0.236ins) dia.</p> <p>120°</p> <p>120°</p> <p>Cable entry</p> <p>← 118 mm dia. →</p>