

## SecuriLED SS20XDV/LED

Surface Mount



ECE R65 Approved

## SecuriLED SB20XDV/LED

Bracket Mount



>200cd (amber) >200cd (red) >100cd (blue) >200cd (white)	120/min	quad flash	400mA (1.5A Peak)	200mA (750mA Peak)	IP67	370gms

### Features:

Surface mount or bracket mount quad flash LED directional.

- Intensely bright 3rd generation LEDs
- Dual voltage 12/24V (10 – 30Vdc)
- Multiple beacons may be connected together to provide synchronous or alternate flash patterns
- Bracket mount version adjusts horizontally and vertically
- Ultra low power consumption
- Integral electronics – no need for separate power pack or control unit
- IP67 rated
- 3 year guarantee

Certified to EMC directive 2004/104/EC.

CE – complies with EMC Directive 89/336/EEC.

Certified to ECE R65 (amber and blue).

Certified to PITO ACS 5.

High voltage transient and polarity reversal protection fitted.

Operating temperature: –30°C to +55°C (–30°C lower limit subject to intermittent and non-continuous use at temperatures below –20°C).



### Applications:

Suitable for many vehicle applications including fleet, cars, delivery, refuse trucks, large vehicles, road maintenance, recovery, utilities and road safety.

### Materials:

Polycarbonate lens, Aluminium base coated black.

Amber	Red	Blue	White
497032	497033	497034	497031

Amber	Red	Blue	White
497042	497043	497044	497041