

Turbo Star ELU2DXDV/15

ECE R65 Approved



Certified to EMC directive 2004/104/EC.

CE – complies with EMC Directive 89/336/EEC.

Certified to ECE R65.

High voltage transient and polarity reversal protection fitted.

Operating temperature: -30°C to $+55^{\circ}\text{C}$ (-30°C lower limit subject to intermittent and non-continuous use at temperatures below -20°C).



>100cd (amber) >42cd (blue)	120/min	double flash	1.25A	600mA	IP65	0.45kg

Features:

A high powered Xenon beacon with an inner fresnel lens and a smooth easy-clean outer lens.

- Automatically adjusts to both 12V and 24V (11.5 – 30Vdc)
- Homologated to ECE R65
- Up to 4 beacons can be synchronised
- 3,000 hours tube life
- 12 months' guarantee

Applications:

Suitable for all vehicles including large vehicles, refuse trucks, recovery, fleets, highway maintenance and emergency services.

Materials:

Polycarbonate lens, ABS base.

Lens Colour	Three Bolt	Magnetic	Pole Mount
Amber	470042	470045	470047
Blue	470044	470046	470048
Drilling for Panel Mounting (ISO 4148 / DIN 14620) 4 holes 7mm dia. Cable entry 130 mm dia.			

Non ECE R65 Approved Versions	Red Lens	Clear Lens	Green Lens
ELB2DXDV/15	470053	470051	470055

See page 43 for accessories.